

## **13.00 Floor Finishes**

### **13.01 Colours**

Colours of all floor finishes shall form part of the overall colour scheme and maintainability for the building.

Light colours should not be used in high traffic areas or adjacent to external entries.

Colours and patterns to carpet and vinyl finishes shall be selected from the nominated

### 13.03 Vinyl Finishes

Vinyl shall only be used in those areas as noted on the SDFs, and shall be **Tarkett** 'Emminent', **Armstrong** 'Accolade' or **Polyfloor** 'Classic Mystique PUR'. All vinyl finishes in an individual

All tiles shall comply with the following criteria:

Physical Properties	Standard	Values
Surface qualities	ISO 10545-2	Length and width + or - 0.6% Warpage of edges + or - 0.5% Thickness + or - 0.5% Wedging + or - 0.6% Flatness + or - 0.5%
Water Absorption	ISO 10545-3	> 0.5%
Modulus of Rupture	ISO 10545-4	• 27 N/mm <sup>2</sup>
Deep Abrasion	ISO 10545-6	> 205 mm <sup>2</sup>
Coefficient of Linear or Thermal Expansion	ISO 10545-8	> 9 <sup>0</sup> K <sup>-1</sup>
Resistance to Thermal Shock	ISO 10545-9	No visible defects
Moisture Expansion	ISO 10545-10	> 0.05%
Crazing Resistance	ISO 10545-11	No visible defects
Chemical Resistance	ISO 10545-13	No visible defects
Resistance to Stains	ISO 10545-14	No visible defects
Slip Resistance	AS/NZS 4586	Refer to 'An Introductory Guide to Slip Resistance of Pedestrian Surface Materials' HB 197:1999 published by CSIRO & Standards Australia

