

Group Study Room (Learning Centre):	Whiteboard 1200mm long Pinboard 1200mm long
Computer Work Area (Learning Centre):	Pinboard 2100mm long in vicinity of main entry Pinboard 1200mm long at or near the printers
Other Occupied Areas:	Noteboard 600mm x 400mm high outside room entry door adjacent to the door frame and mounted at 1350mm from the floor to the bottom edge of the board

15.03 Bookshelves

Particular requirements for bookshelves throughout the building shall be as set out in the SDFs. The minimum quantity of shelving to each faculty office shall be 24m unless noted otherwise and shall be fully adjustable.

Unless nominated otherwise in the SDFs, shelving shall be white melamine finished Craftwood with glued edge strips all round, 300mm wide and supported on a white prefinished 'U-rect-it' keyhole strip and bracket system.

Shelving to PVC or Head of School offices shall be Tasmanian Oak veneer finish.

No other colour of shelving or support components are to be specified unless approved by the Superintendent.

15.06 Built-in Joinery Generally

Built-in joinery units such as cupboards and laboratory benches shall be provided as noted on the SDFs.

Details shall be determined in conjunction with CLF, and GU Standard Detail Drawings shall be used as a guide only.

All built-in furniture units shall have a recessed base finished in satin black laminate.

Where abutting walls, provide an integral splashback not less than 150mm high, sealed to the wall.

All cupboards and drawer units shall be lockable and master keyed (not keyed alike).

Where a timber finish is selected for built-in furniture, a graded Tasmanian Oak timber veneer or a Beech melamine finish shall be used. All other built-in cupboards, benches, etc. shall have a durable coloured laminated plastic finish of colours to be approved by the Users. The use of White laminate on bench tops is discouraged.

15.07 Lecture Theatres

Lecture theatres shall be fitted out with all benches, desks, lecterns and fixed seating as required by the SDFs.

Seating - Fixed seating with tablet arms shall be equal to 'Fagaleo Studia' series with 'Wrimatic' tablet arm with upholstered seat and back pads. The selection of seat type is to be approved by OFM.

People with disabilities - Provision shall be made to accommodate people with disabilities by provision of spaces for wheelchairs with writing benches which are designed in accordance with the Australian Standard. The location of these spaces should be distributed around the Theatre

15.11 Kitchenettes and Tea Preparation Stations

Bench cupboard units to kitchenettes in Staff Common Rooms and to Tea Preparation stations shall be as previously described with laminate bench tops and splashbacks generally in accordance with GU Standard Detail Drawing GSD-302, with provision for a dishwasher, microwave oven or refrigerator if nominated in the SDFs. Microwaves shall be mounted on a wall

In the design of laboratory fitments, consideration must be given to providing access for people with disabilities.

Vanity bench unit with full width mirror as per GU Standard Detail Drawing No. GSD-405 (only where directed by CLF)

Wall basin splashback panel/duct to match wall panelling with 250mm wide hinged shelf/lid at 1200mm above f.f.l. (detail to be provided by CLF)

Mirror panel 800mm high of width to match splashback panel to each basin.

- 'Pallmall Clear Vu Encore' soap dispenser Part No. 9330 on the splashback over each basin.

'Xlerator Model XL-W' surface mounted automatic electric hand dryer with white epoxy painted cover.

Coat Hooks (c.p.), 2 No.

Toilet Cubicles and Urinals:

'Bradley 756' stainless steel (304) shelf with satin finish 500 mm long, mounted on the wall with 20mm matching cylindrical spacers, between urinals and above WC cisterns for the placement of books, handbags etc by persons using the facilities.

'Bowscott Jumboline' Impact resistant ABS toilet roll dispenser.

Door bumper and hook to cubicle door (c.p.).

Unisex toilet for people with disabilities:

Grab rails as required by AS 1428.1

300mm long Grab rail to back of outward opening door as a pull handle

Aluminium framed mirror 600 x 1000mm high with bottom edge abutting top of wash basin approx. 800mm above f.f.l.

'Pallmall Clear Vu Encore' soap dispenser Part No. 9330. Do not locate within 500mm of a side wall.

'Bradley 756' stainless steel (304) shelf with satin finish 500 mm long, mounted on the wall with 20mm matching cylindrical spacers

'Bradley 2291-11' surface mounted paper towel dispenser/waste receptacle.

'Bradley 5224' dual toilet roll holder

Coat Hook (c.p.), 2 No.

'J & D MacDonald' wall mounted folding baby change table (at Ground Level of building only)

Shower recess:

'Bradley 900' soap holder in accordance with AS 1428.1

Coat hooks (cp), 2 No.

Grab rails in accordance with AS 1428.1

'L&M BTSS -960SL' wall mounted stainless steel folding slatted bench seat

'Monotrack D9180 Shower Bend' pre-bent curtain rail with mid hanger and white nylon curtain or sliding glazed shower screen door if nominated by the SDF's.

'Bradley 756' stainless steel (304) shelf 500 mm long as previously described.

15.16 Hand Wash Stations

Provide the following to hand wash wall basins in laboratories or clinical spaces;

Compact Laminate splashback panel approx. 900 x 1650mm high with bottom edge to align with top of skirting

'Bradley 2291-11' surface mounted paper towel dispenser/waste receptacle mounted on splashback.

'Pallmall Clear Vu Encore' soap dispenser Part No. 9330 mounted on the splashback over each basin. Ensure that soaps drips over basin and not onto the floor.

15.17 Coat Hooks

In addition to those required in toilet areas, provide a coat hook on the back of all office doors in

for each occupant in a laboratory. All coathooks shall be mounted at 1750mm above finished floor level.

15.18 Mail Boxes, Assignment Boxes, Enquiry Counters

For all Reception/General Offices provide lockable/secure enquiry counters designed so as not to adversely affect the operation of air-conditioning. Such counters shall be fitted with adjustable shelves below the counter and adjustable computer work tops and shall provide for disabled access.

Adjacent to General Office areas, provide lockable mailboxes and assignment return boxes in accordance with the requirements stated in the SDFs and GU Standard Detail Drawings

The spout outlet shall be of sufficient height above the bowl to allow a standard 220mm high water bottle to be held vertically under the shroud. A sign stating 'Bottle Filling Only' shall be applied to the stainless steel wall panel above the bowl. The number of bottle filling points shall be determined in conjunction with CLF.

Refer to [Sections 17.00](#) and [20.00](#) for connections to services.

15.22 Works of Art

Liaison with the Director, Griffith Artworks, should occur at an early date in the development of the plans to designate 'gallery' areas in public spaces such as corridors, foyers and meeting rooms. These walls to be kept clear of notice boards and other fittings such as clocks, power points, phones, drinking fountains, air conditioning equipment etc.

In all designated 'gallery' areas, install hanging tracks to the length of the wall. The track shall be 'CAPRAL EOO229A1605650' extruded aluminium section sail rope track with anodised clear finish. The track is available in 6.5 metre lengths.

Ensure that access to the track channel and butted pieces allow for the smooth passage of the slider lugs.

Where a purpose built Gallery for the display of artworks is intended, all specialist fittings required will be nominated in the SDF.